

# `structview.sty`: Structures and Views in $\text{\S T E X}^*$

Michael Kohlhase  
Jacobs University, Bremen  
<http://kwarc.info/kohlhase>

April 7, 2016

## **Abstract**

The `structview` package is part of the  $\text{\S T E X}$  collection, a version of  $\text{T E X}/\text{\La T E X}$  that allows to markup  $\text{T E X}/\text{\La T E X}$  documents semantically without leaving the document format, essentially turning  $\text{T E X}/\text{\La T E X}$  into a document format for mathematical knowledge management (MKM).

This package supplies infrastructure for OMDOC structures and views: complex semantic relations between modules/theories.

---

\*Version v1.4 (last revised 2016/04/06)

# Contents

<b>1</b>	<b>Introduction</b>	<b>3</b>
<b>2</b>	<b>The User Interface</b>	<b>3</b>
2.1	Package Options . . . . .	3
2.2	Structures . . . . .	3
2.3	Views . . . . .	4
<b>3</b>	<b>Limitations &amp; Extensions</b>	<b>4</b>
<b>4</b>	<b>The Implementation</b>	<b>5</b>
4.1	Package Options . . . . .	5
4.2	Structures . . . . .	5
4.3	Views . . . . .	5

EdN:1

# 1 Introduction

1

# 2 The User Interface

The main contributions of the `modules` package are the `module` environment, which allows for lexical scoping of semantic macros with inheritance and the `\symdef` macro for declaration of semantic macros that underly the `module` scoping.

## 2.1 Package Options

EdN:2

- `showmods` The `modules` package takes two options: If we set `showmods`<sup>2</sup>, then the views (see Section 2.3) are shown. If we set the `qualifiedimports` option, then qualified imports are enabled. Qualified imports give more flexibility in module inheritance, but consume more internal memory. As qualified imports are not fully implemented at the moment, they are turned off by default see Limitation ??.
- `qualifiedimports`
- `noauxreq` The option `noauxreq` prohibits the registration of `\@requiremodules` commands in the `aux` file. They are necessary for preloading the module signatures so that entries in the table of contents can have semantic macros; but as they sometimes cause trouble the option allows to turn off preloading.
- `showmeta` If the `showmeta` is set, then the metadata keys are shown (see [Koh15] for details and customization options).

## 2.2 Structures

EdN:3

- `importmodulevia` The `\importmodule` macro has a variant `\importmodulevia` that allows the specification of a theory morphism to be applied. `\importmodulevia{<thyid>}{<assignments>}` specifies the “source theory” via its identifier `<thyid>` and the morphism by `<assignments>`. There are four kinds:<sup>3</sup>
- `\vassign` **symbol assignments** via `\vassign{<sym>}{<exp>}`, which defines the symbol `<sym>` introduced in the current theory by an expression `<exp>` in the source theory.
- `\fassign` **function assignments** via `\fassign{<bvars>}{<pat>}{<exp>}`, is a variant which defines a function symbol `<sym>` introduced in the current theory by mapping a pattern expression `<pat>` (`<sym>` applied to `<bvars>`) to an expression `<exp>` in the source theory on bound variables `<bvars>`.
- `\tassign` **term assignments** via `\tassign[<source-cd>]{<tname>}{<source-tname>}`, which assigns to the term with name `<tname>` in the current theory a term with name `<source-tname>` in the theory `<source-cd>` whose default value is the source theory.

<sup>1</sup>EdNOTE: What are structures and views?

<sup>2</sup>EdNOTE: This mechanism does not work yet, since we cannot disable it when importing modules and that leads to unwanted boxes. What we need to do instead is to tweak the `sms` utility to use an internal version that never shows anything during `sms` reading.

<sup>3</sup>EdNOTE: MK: this needs to be consolidated and researched better.

`\ttassign` **term text assignments** via `\tassign{⟨tname⟩}{⟨text⟩}`, which defines a term with name `⟨tname⟩` in the current theory via a definitional text.

```

\begin{module}[id=ring]
\begin{importmodulevia}{monoid}
  \vassign{rbase}\magbase
  \fassign{a,b}{\rtimes{A}B}{\magmaop{a}b}
  \vassign{rone}\monunit
\end{importmodulevia}
\symdef{rbase}{G}
\symdef[name=rtimes]{rtimesOp}{\cdot}
\symdef{rtimes}[2]{\infix\rtimesOp{#1}{#2}}
\symdef{rone}{1}
\begin{importmodulevia}{cgroup}
  \vassign{rplus}\magmaop
  \vassign{rzero}\monunit
  \vassign{rinvOp}\cginvOp
\end{importmodulevia}
\symdef[name=rplus]{rplusOp}{+}
\symdef{rplus}[2]{\infix\rplusOp{#1}{#2}}
\symdef[name=rminus]{rminusOp}{-}
\symdef{rminus}[1]{\infix\rminusOp{#1}{#2}}
...
\end{module}

```

**Example 1:** A Module for Rings with inheritance from monoids and commutative groups

## 2.3 Views

A view is a mapping between modules, such that all model assumptions (axioms) of the source module are satisfied in the target module. <sup>4</sup>

EdN:4

## 3 Limitations & Extensions

In this section we will discuss limitations and possible extensions of the `modules` package. Any contributions and extension ideas are welcome; please discuss ideas, requests, fixes, etc on the  [\$\LaTeX\$  TRAC \[sTeX:online\]](#).

<sup>4</sup>EdNOTE: Document and make Examples

## 4 The Implementation

### 4.1 Package Options

We declare some switches which will modify the behavior according to the package options. Generally, an option xxx will just set the appropriate switches to true (otherwise they stay false). The options we are not using, we pass on to the `sref` package we require next.

```
1 ⟨*package⟩
2 \newif\if@structview@mh@\@structview@mh@false
3 \DeclareOption{mh}{\@structview@mh@true
4 \PassOptionsToPackage{\CurrentOption}{modules}}
5 \DeclareOption*{\PassOptionsToPackage{\CurrentOption}{modules}}
6 \ProcessOptions
```

The next measure is to ensure that the `sref` and `xcomment` packages are loaded (in the right version). For L<sup>A</sup>T<sub>E</sub>X<sub>M</sub>L, we also initialize the package inclusions.

```
7 \if@structview@mh\RequirePackage{structview-mh}\fi
8 \RequirePackage{modules}
```

### 4.2 Structures

`\importmodulevia` The `importmodulevia` environment just calls `\importmodule`, but to get around the group, we first define a local macro `\@@doit`, which does that and can be called with an `\aftergroup` to escape the environment grouping introduced by `importmodulevia`.

```
9 \newenvironment{importmodulevia}[2] []{%
10 \gdef\@@doit{\importmodule[#1]{#2}}%
11 \ifmod@show\par\noindent importing module #2 via \@@doit\fi%
12 }{%
13 \aftergroup\@@doit\ifmod@show end import\fi%
14 }%
```

`\*assign`

```
15 \newrobustcmd\vassign[3] []{\ifmod@show\ensuremath{#2\mapsto #3}, \fi}%
16 \newrobustcmd\tassign[3] []{\ifmod@show #2\ensuremath{\mapsto} #3, \fi}%
17 \newrobustcmd\fassign[4] []{\ifmod@show \ensuremath{#3\mapsto #4}, \fi}%
18 \newrobustcmd\ttassign[3] []{\ifmod@show #2\ensuremath{\mapsto} ‘‘#3’’, \fi}%
```

### 4.3 Views

We first prepare the ground by defining the keys for the `view` environment.

```
19 \srefaddidkey{view}
20 \addmetakey*{view}{title}
21 \addmetakey{view}{display}
22 \addmetakey{view}{from}
23 \addmetakey{view}{to}
24 \addmetakey{view}{creators}
```

```

25 \addmetakey{view}{contributors}
26 \addmetakey{view}{srccite}
27 \addmetakey{view}{type}
28 \addmetakey[sms]{view}{ext}

```

`\view@heading` Then we make a convenience macro for the view heading. This can be customized.

```

29 \newcounter{view}[section]
30 \newrobustcmd\view@heading[4]{%
31   \if@importing%
32   \else%
33     \stepcounter{view}%
34     \edef\@display{#3}\edef\@title{#4}%
35     \noindent%
36     \ifx\@display\st@flow%
37     \else%
38       {\textbf{View} {\thesection.\theview} from \textsf{#1} to \textsf{#2}}%
39       \sref@label@id{View \thesection.\theview}%
40       \ifx\@title\@empty%
41         \quad%
42       \else%
43         \quad(\@title)%
44       \fi%
45       \par\noindent%
46     \fi%
47     \ignorespaces%
48   \fi%
49 }%ifmod@show

```

`view` The `view` environment relies on the `@view` environment (used also in the  $\TeX$  module signatures) for module bookkeeping and adds presentation (a heading and a box) if the `showmods` option is set.

```

50 \newenvironment{view}[3] []{%
51   \metasetkeys{view}{#1}%
52   \sref@target%
53   \begin{@view}{#2}{#3}%
54   \view@heading{#2}{#3}{\view@display}{\view@title}%
55 }{%
56   \end{@view}%
57   \ignorespaces%
58 }%
59 \ifmod@show\surroundwithmboxed{view}\fi%

```

`@view` The `@view` does the actual bookkeeping at the module level.

```

60 \newenvironment{@view}[2]{%from, to
61   \@importmodule[\view@from]{#1}{\view@ext}%
62   \@importmodule[\view@to]{#2}{\view@ext}%
63 }{}%

```

`viewsketch` The `viewsketch` environment behaves like `view`, but only has text contents.

```

64 \newenvironment{viewsketch}[3] []{%
65   \metasetkeys{view}{#1}%
66   \sref@target%
67   \begin{@view}{#2}{#3}%
68   \view@heading{#2}{#3}{\view@display}{\view@title}%
69 }{%
70   \end{@view}%
71 }%
72 \ifmod@show\surroundwithmdframed{viewsketch}\fi%

```

EdN:5            \obligation    The \obligation element does not do anything yet on the latexml side.<sup>5</sup>

```

73 \newrobustcmd\obligation[3] []{%
74   \if@importing%
75   \else Axiom #2 is proven by \sref{#3}%
76   \fi%
77 }%
78 </package>

```

---

<sup>5</sup>EDNOTE: document above