

The langscibook L^AT_EX class

Sebastian Nordhoff

Language Science Press Guidelines



Contents

1	Introduction	1
2	The class	3
3	Requirements	5
3.1	Fonts	5
3.2	Styles	5
3.3	Colors and series definitions	5
4	Creating a book	7
4.1	Creating a monograph	7
4.2	Creating an edited volume	8
4.3	Creating a paper for an edited volume	8
5	Creating a dust jacket	9
6	Options	11
6.1	Flag options	11
6.1.1	biblatex	11
6.1.2	bibtex	11
6.1.3	collection	11
6.1.4	collectionchapter	11
6.1.5	collectiontoclong	11
6.1.6	draftmode	11
6.1.7	openreview	12
6.1.8	modfonts	12
6.1.9	multiauthors	12
6.1.10	newtxmath	12
6.1.11	nobabel	12
6.1.12	nonflat	12
6.1.13	showindex	12
6.1.14	smallfont	12

Contents

6.2	String options	13
6.2.1	output	13
6.2.2	spinewidth	13
6.2.3	booklanguage	13
6.2.4	copyright	13
6.3	Metadata commands	13
6.3.1	\BackBody	14
6.3.2	\BackTitle	14
6.3.3	\BookDOI	14
6.3.4	\ChapterDOI	14
6.3.5	\dedication	14
6.3.6	\ISBNdigital	14
6.3.7	\ISBNhardcover	14
6.3.8	\ISBNsoftcover	15
6.3.9	\ISBNsoftcoverus	15
6.3.10	\Series	15
6.3.11	\SeriesNumber	15
6.3.12	\URL	15
6.4	Overrides	15
6.4.1	\SpineAuthor	15
6.4.2	\SpineTitle	15
6.5	Command redefinitions	16
6.5.1	\lsAdvertisement	16
6.5.2	\lsBackBodyFont	16
6.5.3	\lsBackTitleFont	16
6.5.4	\lsCopyright	16
6.5.5	\lsCoverAuthorFont	16
6.5.6	\lsCoverSubTitleFont	16
6.5.7	\lsCoverTitleFont	16
6.5.8	\lsEditorPrefix	17
6.5.9	\lsFontSize	17
6.5.10	\lsImpressumCitationText	17
6.5.11	\lsISSN	17
6.5.12	\lsLanguageIndexTitle	17
6.5.13	\lsNameIndexTitle	17
6.5.14	\lsSpineAuthorFont	17
6.5.15	\lsSpineTitleFont	17
6.5.16	\lsSubjectIndexTitle	18

6.6	Additions	18
6.6.1	\lsAdditionalFontsImprint	18

1 Introduction

This document describes the \LaTeX class langscibook.cls. This class is used for typesetting books with Language Science Press. Language Science Press publish open access monographs and edited volumes in linguistics.

2 The class

The class is loaded via `\documentclass{langscibook}`. The standard use case is the creation of a book. If used without an `output=` option, the option `output=book` is loaded. The class can also be used to create dust jackets for books with different measurements via the output option values `covercreatespace` (for <http://www.createspace.com>) and `coverbodsc/coverbodhc` (for <http://www.bod.de>).

The class provides for the following:

- front cover
- frontispiece
- inside title
- colophon
- table of contents
- chapters
- list of references (per chapter or global)
- name index, subject index, language index
- advertisement
- back title
- ISBN
- DOI (per book and per chapter)

When used to create dust jackets, the class will produce a large pdf with a collation of backcover, spine and frontcover, from left to right, surrounded by bleed.

3 Requirements

3.1 Fonts

The class uses the fonts Libertine, Arimo and Dejavu. These have to be present on the system.

3.2 Styles

A couple of additional style files come with the class. Documents using this class will compile without them, but in order to typeset books for Language Science Press, these packages should be loaded as well. These packages are

- `langsci-basic.sty`: Commands used in all Language Science Press books
- `langsci-optional.sty`: Further commands useful for some typical books
- `langsci-gb4e.sty`: Package for linguistic examples
- `langsci-cgloss.sty`: Helper package for `langsci-gb4e`
- `langsci-forest-setup.sty`: Set up the forest package for linguistic trees
- `langsci-tbls.sty`: Package for the textbook series Textbooks in Language Sciences
- `langsci-bidi.sty`: Package for typesetting right-to-left text

3.3 Colors and series definitions

The metadata for Language Science Press book series are stored in the file `langsci-series.def`. This file loads the file `langsci-colors.def` to set the colors for the cover and title font. Both files should be safe to use for all books of well-established series. For new series, the ISSN field of `langsci-series.def` might have to be updated.

4 Creating a book

The easiest way to start a book is to download the skeletons from <http://langsci-press.org/templatesAndTools>. Sample documents for monographs, edited volumes and chapters in edited volumes are provided in the folder `examples/` as well.

4.1 Creating a monograph

Load the class. Make sure the following metadata values are set with the metadata commands listed in §6.3:

- `author`
- `title`

Provide the following additional information if necessary:

- `series`
- `series number`
- `all ISBNs`
- `BookDOI`
- `ID`
- `blurb (back body)`
- `subtitle`
- `backtitle`
- `spine title`
- `spine author`

4 *Creating a book*

- dedication
- list of proofreaders
- list of typesetters
- list of illustrators
- license other than CC-BY
- list of additional fonts

4.2 **Creating an edited volume**

Proceed as for a monograph, but use the option `collection`. Use `\author` for the editor(s). Use the option `multiauthors` if there is more than one editor. You may want to use the further options `collectionchapter` and `collectiontoclong`. Chapters are included via `\includepaper{}`. Set the bibliography resource for all papers in the main file.

4.3 **Creating a paper for an edited volume**

Use the output option `paper`. Provide the following metadata in the preamble:

- `\author with (\affiliation)`
- `\title`
- `\abstract` (optional)

You might want to use `\shorttitlerunninghead` for chapters with very long titles.

5 Creating a dust jacket

Use the option `coverbodhc`, `coverbodsc` or `covercreatespace` and set the option `spinewidth`. Run \LaTeX twice. Upload to the respective websites to see whether the lengths were chosen correctly.

6 Options

The class has flag options to toggle certain behaviour and string options to set metadata values.

6.1 Flag options

6.1.1 **collection**

Make the book an edited volume

Default value: `false`

6.1.2 **collectionchapter**

Add numeric chapter prefix to each contribution.

Default value: `false`

6.1.3 **collectiontoclong**

More detailed table of content in edited volumes

Default value: `false`

6.1.4 **draftmode**

Switch to draft mode (adds: draft stamp, indication of overlong lines, date)

Default value: `false`

6.1.5 **openreview**

Switch to open review mode

Default value: `false`

6.1.6 **modfonts**

Use modified fonts provided by Language Science Press

Default value: `false`

6 Options

6.1.7 **multiauthors**

Set editor suffix to eds. instead of ed.

Default value: false

6.1.8 **newtxmath**

Switch math fonts to newtxmath

Default value: false

6.1.9 **nobabel**

Do not use the Babel package in the class

Default value: false

6.1.10 **nonflat**

Use elaborate directory structure. If set to true, fonts, packages etc will be loaded from subfolders. If set to false, they will be loaded from the working directory

Default value: false

6.1.11 **showindex**

Show indexed terms in margin

Default value: false

6.1.12 **smallfont**

Use a smaller font for books above 500 pages

Default value: false

6.2 String options

6.2.1 **output**

Different output formats

Default value: book

- book: The book with frontcover and backcover
- inprep: Mark manuscript as in preparation

- **paper:** Contribution to edited volume
- **guidelines:** Choose color grey; condense frontmatter
- **coverbodhc:** Create a two-page wide cover (back-spine-front) for use with BoD hardcover books
- **coverbodsc:** Create a two-page wide cover (back-spine-front) for use with BoD softcover books
- **covercreatespace:** Create a two-page wide cover (back-spine-front) for use with CreateSpace

6.2.2 **spinewidth**

The width of the spine (for cover creation)

Default value: 20mm

6.2.3 **booklanguage**

Load babel for the specified language and change the custom headers for list of references and indexes

Default value: english

6.2.4 **copyright**

The license chosen

Default value: "CC-BY"

6.3 Metadata commands

The following commands are used to indicated metadata.

6.3.1 **\BackBody**

Text to be printed on the back cover

Default value: European lingues es membres del sam familie. Lor separat existentie es un myth. Por scientie, musica, sport etc, litot Europa usa li sam vocabular. Li lingues differe solmen in li grammatica, li pronunciation e li plu commun vocabules. Omnicos directe al desirabilite de un nov lingua franca: On refusa continuar payar custosi traductores.

6 Options

6.3.2 \BackTitle

Title on back cover

Default value: same as on front cover

6.3.3 \BookDOI

DOI for the book

Default value: ??

6.3.4 \ChapterDOI

DOI for a chapter

Default value: ??

6.3.5 \dedication

A dedication

Default value: void

6.3.6 \ISBNdigital

ISBN for the digital version

Default value: 000-0-000000-00-0

6.3.7 \ISBNhardcover

ISBN for the hardcover version

Default value: 000-0-000000-00-0

6.3.8 \ISBNsoftcover

ISBN for the softcover version

Default value: 000-0-000000-00-0

6.3.9 \ISBNsoftcoverus

ISBN for the softcover version (US distribution)

Default value: 000-0-000000-00-0

6.3.10 `\Series`

The series this book appears in. Use the acronyms found in `series.def`

Default value: `eotms`

6.3.11 `\SeriesNumber`

Position of the book in its series

Default value: `??`

6.3.12 `\URL`

The URL where this title can be downloaded

Default value: `http://langsci-press.org/catalog`

6.4 Overrides

The following commands allow to override further default settings:

6.4.1 `\SpineAuthor`

Custom author on spine. Useful for long lists of authors/editors

Default value: same as on cover

6.4.2 `\SpineTitle`

Custom title on spine. Useful for long titles

Default value: same as on cover

6.5 Command redefinitions

Redefine the following commands to further alter the appearance:

6.5.1 `\lsAdvertisement`

Specify the advertisement on the last page of the book

Default value: `\include{\logopath didyoulikethisbook}`

6 Options

6.5.2 `\lsBackBodyFont`

Font used for text on back cover

Default value: main font

6.5.3 `\lsBackTitleFont`

Font used for title on back cover

Default value: `\sffamily\addfontfeaturesScale=MatchUppercase
\fontsize{25pt}{10mm}\selectfont`

6.5.4 `\lsCopyright`

Choice of licence

Default value: CC-BY

6.5.5 `\lsCoverAuthorFont`

Font for author/editor on cover

Default value: `\fontsize{25pt}{12.5mm}\selectfont`

6.5.6 `\lsCoverSubTitleFont`

Font for the subtitle

Default value: `\sffamily\addfontfeatures{Scale=MatchUppercase}
\fontsize{25pt}{10mm}\selectfont`

6.5.7 `\lsCoverTitleFont`

Font for the title

Default value: `\sffamily\addfontfeaturesScale=MatchUppercase
\fontsize52pt17.25mm\selectfont`

6.5.8 `\lsEditorPrefix`

How editors are indicated on title page. Useful for localization.

Default value: `\LARGE Edited by\\`

6.5.9 **\lsFontSize**

size of main font

Default value: 11pt

6.5.10 **\lsImpressumCitationText**

custom citation text, useful for including notes etc.

Default value: computed from author and title fields

6.5.11 **\lsISSN**

ISSN of the series

Default value: ??

6.5.12 **\lsLanguageIndexTitle**

The title of the language index. Change this for non-English works

Default value: Language index

6.5.13 **\lsNameIndexTitle**

The title of the name index. Change this for non-English works

Default value: Name index

6.5.14 **\lsSpineAuthorFont**

Font for the author on the spine

Default value: \fontsize{16pt}{14pt}\selectfont

6.5.15 **\lsSpineTitleFont**

Font for the title on the spine

Default value: \sffamily\fontsize{18pt}{14pt}\selectfont

6.5.16 **\lsSubjectIndexTitle**

The title of the subject index. Change this for non-English works

Default value: Subject index

6 Options

6.5.17 \lsYear

\the\year

Default value:

6.6

Additions

6.6.1 \lsAdditionalFontsImprint

Add additional fonts to the list of fonts in the colophon

Default value: void